

BUSINESS AND FLEET EV CHARGING

PROFESSIONAL AC DOUBLE OUTLET CHARGING



Professional double outlet charging units suitable for wall or ground mounting and available for both single and three phase connection, with an output range from 3kW to 22kW RFID card or mobile phone app access, with on-line monitoring facility for charge point management and billing purposes Open Charge Point Protocol (OCPP) v1.6 compliant, which enables connection to open public/private charging networks. Dynamic load balancing enables the management and sharing of available power.



DIMENSIONS (WALL UNIT)	H 570 D 180 W 320 (MM)
DIMENSIONS (PEDESTAL UNIT)	H 1200 D 200 W 300 (MM)
ENERGY METER	MID APPROVED
MAINS CONNECTION	230V TO 400V 50Hz
CHARGING OUTPUT	3kW TO 22kW AC (single/three phase)
CURRENT PROTECTION	RCD TYPE A 40A MCB TYPE B 40A
SOCKET	TYPE 2 EV SOCKETS
OPERATING TEMPERATURE	-20 DEG C TO +55 DEG C
CHARGEPOINT PROTOCOL	OCPP V1.6
STANDARDS	IEC62196-2 IEC61851 (1) (22)
PROTECTION	IP55 PROTECTED
OUTER CASING	STAINLESS STEEL CASING
COMMUNICATION	GSM GPRS INTEGRATED

