

SUPERFAST DC CHARGING

State of the art fast charging
from 25kW to 150kW



DC 25 WALLBOX



| | |
|------------------------|-------------------------|
| Dimensions | H 812 D 273 W 704 (MM) |
| Material | STAINLESS STEEL 304 |
| IP Rating | IP54 |
| Input Voltage | 400V 50HZ |
| Communication Protocol | OCPP 1.5 AND OCPP 1.6 |
| Connectivity | 3G (STD) LAN (OPTIONAL) |
| DC Power Output | UP TO 25 KW |
| Cable Length | 2.5M |
| Protection | MCB, RDC, SURGE |
| Charging standards | CHADEMO, CCS 2 |
| Screen | 7" COLOUR TOUCH SCREEN |
| Temperature Range | -30 DEG C. -+ 50 DEG C |

DC 50 COMPACT



| | |
|------------------------|-------------------------|
| Dimensions | H 1500 D 635 W 920 (MM) |
| Material | STAINLESS STEEL 204 |
| IP Rating | IP55 |
| Input Voltage | 400V 50HZ |
| Communication Protocol | OCPP 1.5 AND OCPP 1.6 |
| Connectivity | 3G (STD) LAN (OPTIONAL) |
| DC Power Output | 50 KW |
| Cable Length | 4M |
| Protection | MCB, RDC, SURGE |
| Charging standards | CHADEMO, CCS 2 |
| Screen | 7" COLOUR TOUCH SCREEN |
| Temperature Range | -30 DEG C. -+ 50 DEG C |

DC 150 ULTRA



| | |
|------------------------|-------------------------|
| Dimensions | H 2000 D 735 W 998 (MM) |
| Material | STAINLESS STEEL 204 |
| IP Rating | IP54 |
| Input Voltage | 400V 50HZ |
| Communication Protocol | OCPP 1.5 AND OCPP 1.6 |
| Connectivity | 3G (STD) LAN (OPTIONAL) |
| DC Power Output | UP TO 25 KW |
| Cable Length | 2.5M |
| Protection | MCB, RDC, SURGE |
| Charging standards | CHADEMO, CCS 2 |
| Screen | 7" COLOUR TOUCH SCREEN |
| Temperature Range | -30 DEG C. -+ 50 DEG C |

Complete range of Rapid DC Charging units – from an easy to install wall mounted 25kW system to ground mounted super-fast 150kW output, with load management, additional AC charging socket and simultaneous charging facilities.